

IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST CERTIFICATES FOR ELECTRICAL EQUIPMENT (IECEE) CB SCHEME

CB TEST CERTIFICATE

Product

Control and indicating equipment for fire detection and alarm systems with integrated power supply

Name and address of the applicant

INIM ELECTRONICS S.r.l.
Via dei Lavoratori 10, fraz. Centobuchi, 63076 Montepandone (AP)
Italy

Name and address of the manufacturer

INIM ELECTRONICS S.r.l.
Via dei Lavoratori 10, fraz. Centobuchi, 63076 Montepandone (AP)
Italy

Name and address of the factory

INIM ELECTRONICS S.r.l.
Via dei Lavoratori 10, fraz. Centobuchi, 63076 Montepandone (AP)
Italy

Note: When more than one factory, please report on page 2

[Additional information on page 2](#)

Ratings and principal characteristics

115 V-15%+10%, 50/60Hz, 2.2 A / 230Vac -15%+10%, 50/60Hz, 1.1 A
Output: 27.6 V-, 4 A (for external devices), 1.2 A (for battery charger)
(See Test Reports and Additional Sheet)

Trademark / Brand (if any)



INIM

Customer's Testing Facility (CTF) Stage used

Model / Type Ref.

PREVIDIA-C200LZEc - PREVIDIA-C200LZc - PREVIDIA-C200Lc -
PREVIDIA-C100Lc - PREVIDIA-C050Lc
(where "C" identifies the color of enclosure)

Additional information (if necessary may also be reported on page 2)

[Additional information on page 2](#)

A sample of the product was tested and found to be in conformity with

IEC 62368-1:2018

National differences:
EU Group Differences

As shown in the Test Report Ref. No. which forms part of this Certificate

SS24-0100865-02 - SS24-0100865-04

This CB Test Certificate is issued by the National Certification Body

IMQ S.p.A.
Via Quintiliano 43
Milano, 20138
Italy



Date: 2024-11-15

Signature: Giorgio Belussi

**Description of Control and indicating equipment with integrated power supply
Series PREVIDIA-C**

Test Report**Technical data**

SS24-0100865-02	Input: 115 V-15%+10%, 50/60Hz, 2.2 A Output: 27.6 V-, 4 A (for external devices), 1.2 A (for battery charger) with switching power supply model IPS24160GV1
SS24-0100865-04	Input: 230Vac -15%+10%, 50/60Hz, 1.1 A Output: 27.6 V-, 4 A (for external devices), 1.2 A (for battery charger) with switching power supply model IPS24160G