


IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST CERTIFICATES FOR ELECTRICAL EQUIPMENT
(IECEE) CB SCHEME

CB TEST CERTIFICATE

Product	LUMINAIRES FOR EMERGENCY LIGHTING (wall/ceiling/recessed)
Name and address of the applicant	INIM ELECTRONICS S.r.l. VIA DEI LAVORATORI 10 FRAZ. CENTOBUCHI 63076 MONTEPRANDONE AP Italy
Name and address of the manufacturer	INIM ELECTRONICS S.r.l. VIA DEI LAVORATORI 10 FRAZ. CENTOBUCHI 63076 MONTEPRANDONE AP Italy
Name and address of the factory	<input type="checkbox"/> Additional information on page 2 LIXIT S.r.l. VIA DELL'INDUSTRIA 16 FRAZ. PAGLIARE DEL TRONTO 63078 SPINETOLI AP Italy
Ratings and principal characteristics	LED 230V - cl. II - IP42 - with rest mode - risk group: RG1 at 75cm (see Additional Sheet and Test Report)
Trademark (if any)	 inim ELECTRONICS
Customer's Testing Facility (CTF) Stage used	
Model / Type Ref.	Series DEXIA (see Additional Sheet and Test Report)
Additional information (if necessary may also be reported on page 2)	<input type="checkbox"/> Additional information on page 2
A sample of the product was tested and found to be in conformity with	IEC 60598-1:2014, IEC 60598-1:2014/AMD1:2017, IEC 60598-2-22:2014, IEC 60598-2-22:2014/AMD1:2017, IEC 60598-2-2:2011, IEC TR 62778:2014 National differences: EU Group Differences
As shown in the Test Report Ref. No. which forms part of this Certificate	AI20-0055601-03, AI20-0055606-02

This CB Test Certificate is issued by the National Certification Body

IMQ S.p.A.
Via Quintiliano 43, IT-20138 Milano, Italy

DESCRIPTION OF LUMAIRES SERIES DEXIA

<i>Type Ref.</i>	<i>Rated wattage</i>	<i>Number LED</i>	<i>Type and number of battery</i>	<i>Type of operation</i>	<i>Rated duration</i>	<i>Rated lumen output in emergency operation</i>	<i>Rated lumen output in ordinary operation</i>	<i>Type of controller</i>
DXSA240142	7 W	30 White	1 x LiFePO4 3,2 V 3,3 Ah	Maintained / Non-maintained	1 h 1,5 h 2 h 3 h	700 lm 550 lm 450 lm 350 lm	550 lm	Standard
DXSA360142	15 W	30 White	2 x LiFePO4 3,2 V 3,3 Ah	Maintained / Non-maintained	1 h 1,5 h 2 h 3 h	1300 lm 1000 lm 850 lm 650 lm	1000 lm	Standard
DXAA240142	7 W	30 White	1 x LiFePO4 3,2 V 3,3 Ah	Maintained / Non-maintained	1 h 1,5 h 2 h 3 h	700 lm 550 lm 450 lm 350 lm	550 lm	Self-test
DXAA360142	15 W	30 White	2 x LiFePO4 3,2 V 3,3 Ah	Maintained / Non-maintained	1 h 1,5 h 2 h 3 h	1300 lm 1000 lm 850 lm 650 lm	1000 lm	Self-test
DXBA240142	7 W	30 White	1 x LiFePO4 3,2 V 3,3 Ah	Maintained / Non-maintained	1 h 1,5 h 2 h 3 h	700 lm 550 lm 450 lm 350 lm	550 lm	Bus Supervised
DXBA360142	15 W	30 White	2 x LiFePO4 3,2 V 3,3 Ah	Maintained / Non-maintained	1 h 1,5 h 2 h 3 h	1300 lm 1000 lm 850 lm 650 lm	1000 lm	Bus Supervised