


IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST CERTIFICATES FOR ELECTRICAL EQUIPMENT
(IECEE) CB SCHEME

CB TEST CERTIFICATE

Product	LUMINAIRES FOR EMERGENCY LIGHTING (ceiling/recessed)
Name and address of the applicant	INIM ELECTRONICS S.r.l. VIA DEI LAVORATORI 10 FRAZ. CENTOBUCHI 63076 MONTEPRANDONE AP Italy
Name and address of the manufacturer	INIM ELECTRONICS S.r.l. VIA DEI LAVORATORI 10 FRAZ. CENTOBUCHI 63076 MONTEPRANDONE AP Italy
Name and address of the factory	<input type="checkbox"/> Additional information on page 2 LIXIT S.r.l. VIA DELL'INDUSTRIA 16 FRAZ. PAGLIARE DEL TRONTO 63078 SPINETOLI AP Italy
Note: When more than one factory, please report on page 2	
Ratings and principal characteristics	6W max / LED - 230V - cl. II - IP40 - maintained with rest mode - risk group: RG1 (see Additional Sheet and Test Report)
Trademark (if any)	 inim ELECTRONICS
Customer's Testing Facility (CTF) Stage used	
Model / Type Ref.	Series SPOTLED (see Additional Sheet and Test Report)
Additional information (if necessary may also be reported on page 2)	<input type="checkbox"/> Additional information on page 2
A sample of the product was tested and found to be in conformity with	IEC 60598-1:2014, IEC 60598-1:2014/AMD1:2017, IEC 60598-2-22:2014, IEC 60598-2-22:2014/AMD1:2017, IEC 60598-2-2:2011, IEC TR 62778:2014 National differences: EU Group Differences
As shown in the Test Report Ref. No. which forms part of this Certificate	AI20-0055624-02, AI20-0055629-02

This CB Test Certificate is issued by the National Certification Body

IMQ S.p.A.
Via Quintiliano 43, IT-20138 Milano, Italy

DESCRIPTION OF LUMINAIRES SERIES SPOTLED

<i>Type Ref.</i>	<i>Rated wattage</i>	<i>Number LED</i>	<i>Type and number of battery</i>	<i>Type of operation</i>	<i>Rated duration</i>	<i>Rated lumen output in emergency operation</i>	<i>Rated lumen output in ordinary operation</i>	<i>Type of controller</i>
SPSA240140	6 W max	1	1 x LiFePO4 3,2 V 1,5 Ah	Maintained	1 h	300 lm	220 lm	Standard
SPSA240340	6 W max	1	2 x LiFePO4 3,2 V 1,5 Ah	Maintained	3 h	300 lm	220 lm	Standard
SPAA240140	6 W max	1	1 x LiFePO4 3,2 V 1,5 Ah	Maintained	1 h	300 lm	220 lm	Self-test
SPAA240340	6 W max	1	2 x LiFePO4 3,2 V 1,5 Ah	Maintained	3 h	300 lm	220 lm	Self-test
SPBA240140	6 W max	1	1 x LiFePO4 3,2 V 1,5 Ah	Maintained	1 h	300 lm	220 lm	Bus Supervised
SPBA240340	6 W max	1	2 x LiFePO4 3,2 V 1,5 Ah	Maintained	3 h	300 lm	220 lm	Bus Supervised